

J



/

### It's all about concrete rheology! How does rheology effect concrete handling • Rheology is THE critical workability parameter of fresh concrete • At the site, typically measured by slump test • Slump test only relates to yield stress – not enough to understand full mix behavior • does not provide flow characteristics, • Does not indicate whether the mix is cohesive (sticky), likely to segregate or bleed Plastic Viscosity • Two fresh concrete mixes with the same slump may behave quite differently Poor response to vibration Very difficult to pump • Currently no simple method to evaluate viscosity at site Fair response to vibration and pumping >> >> >>

# It's all about concrete rheology!

#### Response to energy input

- Two identical 4" slump, fiber reinforced concrete mixes
- Vibrated for I0 seconds





>> >> >>

10


### MasterEase 5000

### **Effect on Concrete Rheology**

- MasterEase 5000:
  - reduces the stickiness (viscosity) and
  - Stiffness (yield stress) of a mix
- Mixtures can be handled with significantly lower expenditure of energy and effort during:
  - Pumping
  - Placing
  - Consolidating
  - Finishing..

MasterEase 5000 Water Reducing and Conditioning Admixture:

Enhances rheology performance & handling robustness





MasterEase 5000 — The Easy Mix

MASTER®

BUILDERS


On MasterEase 5000

Water-Reducing &

Conditioning Admixture

The Easy Mix

Click to watch video
on Youtube



## MasterEase 5000

### **Water-Reducing and Conditioning Admixture**

- Next Generation polymer
- Designed especially for harsh and sticky concrete mixes
- Versatile use in most concrete applications
- Enhances all fresh concrete **handling** characteristics: from batching at the plant to discharging, pumping, placing, consolidating and finishing on the site.





### MasterEase 5000

#### **Curb & Gutter Applications**

- "Sped up the machine, reduced vibration, and still had better performance."
- "Reduces the friction and drag on the machine, almost lubricating it as it gets moving."
- "Smoother finish with noticeably fewer voids and imperfections."
- "I in. slump moves and extrudes like 2-3 in. slump. Even when the mix looks on the drier side, no need for retempering."
- "Mix is more robust and feels creamier."





>> >> >>

### MasterEase 5000


#### **Paving Applications**


- "Noticeable difference on the edges crispness and sharpness; it held the edge very well."
- "No issues with low slump concrete; possible to consolidate zero slump concrete."
- "Noticeably better aggregate distribution in core sample."
- "Anticipated benefit with the use of difficult materials."
- "Our sand is very coarse for a 1.5" slump paving mix. Had a workable mix without having to add more cement and had much better movement under the paver."




22










## MasterEase 5000 – Summary


#### **Key takeaways**


- Water-reducing and conditioning admixture Type A
- Especially effective in harsh, sticky mixtures with man sand, angular aggregates, Type IL cement and high SCM content
- Enhances all fresh concrete handling characteristics providing:
  - Shorter discharge time (by 10-15 mins)
  - Reduced pump pressure (20-30%) than reference
  - Improved placement and flow
  - Easier compaction, allowing for lower vibration settings
  - Faster extrusion to lay more paving in the same timeframe
  - Improved surface and edge finish
- Increases productivity
- Peace of mind for all stakeholders




**>> >> >>** 











**>> >> >>**